

TURFRx Supreme Flowable

(0-5-4)

GUARANTEED ANALYSIS

Available Phosphate (P ₂ O ₅)	5.00%
Soluble Potash (K ₂ O)	4.00%
Boron (B)	0.14%*
Copper (Cu)	0.3%
Iron (Fe)	0.3%
Manganese (Mn)	0.6%
0.60% Water soluble Manganese	
Molybdenum (Mo)	0.003%**
Zinc (Zn)	0.6%

(Derived from Phosphoric Acid, Potassium Hydroxide, Boric Acid, Copper Sulfate, Ferrous Sulfate, Manganese Sulfate, Sodium Molybdate and Zinc Sulfate)

F001388

Manufactured by:



COSMOCEL®

QUIMICA CREATIVA A SU SERVICIO

COSMOCEL, S.A.

Vía a Matamoros No. 1501,

San Nicolás de los Garza, N.L., México C.P. 66484

Tel. +52 (81) 8625-3100

www.cosmoce.com servicioalcliente@cosmoce.com

Distributed and Guaranteed by:
Redox Chemicals, LLC

RedoxCHEMICALS, LLC
INNOVATIVE PLANT GROWTH TECHNOLOGY

130 S. 100 W.
Burley, Idaho, USA 83318
208-678-2610

www.redoxchem.com



*WARNING Boron: The use of the fertilizing material containing Boron on any crops other than those recommended may result in serious injury to the crop(s).

**WARNING Molybdenum: The application of fertilizing materials containing molybdenum (Mo) may result in forage crops containing levels of molybdenum (Mo) which are toxic to ruminant animals.

KEEP OUT OF REACH OF CHILDREN

STOP, READ THE LABEL BEFORE USING THIS PRODUCT

COMPATIBILITY:

Always check for compatibility with other products prior to use.

GENERAL INFORMATION:

TurfRx Supreme Flowable is a liquid formulation, developed as an easy to use formulation that is compatible with most fertilizers in spray applications.

APPLICATION RATES

Application	Rate	Comments
Soil	128 to 160 oz per acre Or 2.9 to 3.7 oz per 1,000 ft ²	<ul style="list-style-type: none"> ➤ Spray on the soil surface and water into root zone within 12 hours ➤ Applied weekly to biweekly

Application	Rate	Comments
Foliar	64 to 128 oz per acre Or 1.5 to 2.9 oz per 1000ft ²	<ul style="list-style-type: none"> ➤ Spray on to the leaf and allow to dry. ➤ Applied weekly

IN MISSISSIPPI THIS
PRODUCT IS A LOW
ANALYSIS FERTILIZER

APPLICATION GUIDELINES

- Proper application rates and frequency should be determined by specific conditions and plant requirements.
- Always jar test before adding to a spray tank or injection tank.
- Spray and fertigation applications should be made with sufficient water, 30 mesh screens, and agitation throughout the application.
- When tank mixing with other chemicals, it is the responsibility of the end-user to assume compatibility and safety.
- Poly in-line filters should be replaced with stainless steel, when possible.
- Always consult your agronomist.

AVOID CONTACT WITH SKIN, EYES OR CLOTHING. In case of contact immediately flush skin, eyes or clothing with plenty of water for several minutes.

WARRANTY: Since weather, plants, soils and other ecological conditions may vary, the seller makes no warranty of any kind, express or implied concerning the use of this product. The user assumes all risk of use and handling whether or not in accordance with directions or suggestions.

NET CONTENTS & NET WEIGHT	<input type="checkbox"/> 2.5 Gal <input type="checkbox"/> 9.5 Lt <input type="checkbox"/> 24.88 Lbs <input type="checkbox"/> 11.3 Kg	<input type="checkbox"/> 5.0 Gal <input type="checkbox"/> 19.0 Lts <input type="checkbox"/> 49.76 Lbs <input type="checkbox"/> 22.6 Kgs	<input type="checkbox"/> 275 Gal <input type="checkbox"/> 1040 Lt <input type="checkbox"/> 2736 Lbs <input type="checkbox"/> 1243 Kg	Pounds per gallon at 68 degrees Fahrenheit: 9.95

Caution: The products manufactured by Redox Chemicals, LLC are sold only thru licensed distributors. To insure proper mixing and application, consult with trained Redox Chemicals, LLC distributors. Visit www.redoxchem.com for a list of trained and authorized Redox Chemicals, LLC distributors.

Information regarding the contents and levels of metals in this product is available on the internet at <http://www.aapfco.org/metals.htm> N.P. 1104761 R-5

The Power of Nature