

APPLICATION GUIDELINES:

- Proper application rates and frequency should be determined by specific conditions and plant requirements.
- Supra is highly compatible with most plant nutrients.
- Always jar test before adding to a spray tank or injection tank.
- Spray and fertigation applications should be made with sufficient water, 50 mesh screens and agitation throughout the application.
- When tank mixing with other chemicals, it is the responsibility of the end-user to assure compatibility and safety.
- Poly-in-line filters should be replaced with stainless steel, if possible.
- Always consult your agronomist.

APPLICATION RATES:

APPLICATION	RATE
Foliar	0.25-0.5 gal./acre

Redox products should be stored in a cool dry place, out of direct sunlight. To maintain product quality, storage temperatures should be between **50°F** and **90°F**. Always store liquid products on lower shelves and dry products on higher shelves. Do not stack palletized products. **Open containers must be resealed for storage.** Strictly adhering to Redox storage guidelines will ensure efficacy and performance for the life of the product. If you have a question about the storage, disposal, or shelf-life of your Redox product, contact your local Redox representative or call 1-208-678-2610.

Redox

DISTRIBUTED AND GUARANTEED BY:
REDOX CHEMICALS, LLC

130 S. 100 W.
BURLEY, IDAHO, USA 83318
208.678.2610
WWW.REDOXCHEM.COM

MANUFACTURED BY:



COSMOCEL[®]
COSMOCEL S.A.
VIA A MATAMOROS NO. 1501,
SAN NICOLAS DE LOS GARZA, N.L.,
MEXICO C.P. 66484
TEL. +52 (81) 8625-3100
WWW.COSMOCEL.COM
SERVICIOCLIENTES@COSMOCEL.COM



**KEEP OUT OF REACH OF CHILDREN
HARMFUL IF SWALLOWED**

SHAKE OR AGGITATE WELL BEFORE USE

Supra

1-2-2

GUARANTEED ANALYSIS

Total Nitrogen (N).....	1.0%
0.1%..... Urea Nitrogen	
0.9%..... Ammoniacal Nitrogen	
Available Phosphate (P ₂ O ₅).....	2.0%
Soluble Potash (K ₂ O).....	2.0%
Boron (B).....	0.03%
Copper (Cu).....	1.0%
Iron (Fe).....	1.5%
Manganese (Mn).....	1.0%
Molybdenum (Mo).....	0.004%
Zinc (Zn).....	2.0%

DERIVED FROM UREA, ANHYDROUS AMMONIA, PHOSPHORIC ACID, POTASSIUM HYDROXIDE, BORIC ACID, COPPER SULFATE, FERROUS SULFATE, MANGANESE SULFATE, AMMONIUM MOLYBDATE AND ZINC SULFATE

WARNING Boron: The use of the fertilizing material containing Boron on any crops other than those recommended may result in serious injury to the crops(s).

WARNING Molybdenum: The application of fertilizing materials containing molybdenum (Mo) may result in forage crops containing levels of molybdenum (Mo) which are toxic to ruminant animals.

F001388

GENERAL INFORMATION:

Supra is a liquid formula, developed as an easy to use formulation that is compatible with most fertilizers and foliar sprays.

LIMITED WARRANTY AND DISCLAIMER

Limited Warranty: Redox Chemicals, LLC ("Redox") warrants that: (a) the product conforms to the chemical description on the label; and (b) the product is reasonably fit for the purposes set forth in the directions for use, subject to the inherent risks referred to therein, when it is used in accordance with such directions. Tests have not been conducted on all varieties of food crops and plants, or in all states, or under all conditions.

Limitation of Remedies: Buyer's exclusive remedy and Redox's obligation under this Limited Warranty for any and all claims, losses, damages or injuries resulting from the use or handling of this product, whether based in contract, negligence, strict liability or otherwise, shall be limited, at Redox's option, to a replacement or refund for the purchase price of the product used.

In no case shall Redox be liable for any special, incidental, or consequential damages based upon breach of warranty, breach of contract, negligence, strict liability, or any other legal theory. Such damages include, but are not limited to, loss of profits, loss of savings or revenue, cost of any equipment, facilities or services, downtime, the claims of third parties including customers, and injury to property.

No Other Warranties: This limited warranty is understood to be the complete and exclusive agreement between the parties, superseding all prior agreements, oral or written, and all other communications between the parties relating to the subject matter of this agreement. No employee of Redox or any other party is authorized to make any warranty in addition to those made in this agreement. The limited warranty may be varied only by agreement in writing signed an authorized representative of Redox.

Disclaimer of Warranty: THE ABOVE LIMITED WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH EXTENDS BEYOND THE WARRANTY SPECIFIED ABOVE, AND IN NO EVENT SHALL THIS WARRANTY BE DEEMED TO COVER INCIDENTAL OR CONSEQUENTIAL DAMAGES OF ANY KIND.

Venue and Choice of Law: Any claims arising from this limited warranty shall be resolved in the State of Idaho and Idaho law will apply to any dispute.

The products manufactured by Redox Chemicals, LLC are sold only thru licensed distributors. To insure proper mixing and application, consult with trained Redox Chemicals, LLC distributors.

Information regarding the contents and levels of metals in this product is available on the internet at: <http://www.aapfco.org/metals.htm>

NET CONTENTS & NET WEIGHT

Weight per gallon at 68°
Fahrenheit, 10.52 Lbs.

1.25 Gals. (4.73 Lts.) 13.2 Lbs. (6.0 Kgs.)	5 Gals. (18.92 Lts.) 52.8 Lbs. (23.95 Kgs.)
--	--

04/17

N.P. 2104291 Rev. 2